

PMX40 RF Power Meter



PMX40 RF Power Meter



The PMX40 provides design engineers and technicians the utility of traditional benchtop instrument, the flexibility and performance of modern USB RF power sensors, and the simplicity of a multi-touch display built with Boonton award-winning technology.

As a benchtop meter, the PMX40 provides a standalone solution for capturing, displaying, and analyzing peak and average RF power in both the time and statistical domains through an intuitive, multi-touch touchscreen display.

The PMX40 Power Meter utilizes up to four RTP and CPS families of USB RF power sensors with industry-leading performance and capabilities either independently or for synchronized multi-channel measurements of CW, modulated, and pulsed signals.

Providing the ultimate flexibility, the PMX40 sensors can be disconnected and independently used as standalone instruments.


Key Features

- Capture/display/analyze peak and average power
- Frequency range from 4 kHz to 40 GHz
- **Industry-leading** video bandwidth (195 MHz) and rise time (3 ns)
- **Industry-leading** 100,000 measurements per second
- **Industry-leading** 100 ps time resolution
- Synchronous multi-channel measurements (up to 4 channels)
- Sensors can be used as standalone instruments




PMX40 RF Power Meter – Front Panel

The PMX40's intuitive, multi-touch display enables fast configuration of up to four sensors as well as easy access to measurement and analysis tools, providing a standalone solution for capturing, displaying, and analyzing peak and average RF power in both the time and statistical domains. The meter also incorporates a test source to verify sensor operation.




- 1 Connect up to 4 USB sensors for multi-channel measurements.
- 2 Sync ports to source or receive triggers for timing and synchronization.
- 3 Test source to verify sensor operation.
- 4 Multi-touch display with intuitive user interface.
- 5 One touch to quickly access presets and favorite functions.

6 PMX40 Measurement Modes




Continuous Mode

For simple, intuitive measurements of repetitive waveforms, the PMX40 Continuous Mode of operation provides a numeric display of average, maximum and minimum signal powers.



Pulsed Mode

Analysis of fast-rising single pulses or pulses with short pulse repetition intervals (PRIs) requires an instrument with sophisticated trigger and data acquisition capability. Within Pulsed Mode, more than 16 pulse parameters can be measured.



Statistical Mode

In Statistical Mode, the PMX40 plots the Complementary Cumulative Distribution Function (CCDF). The CCDF plot shows the rate of occurrence of a specific crest factor for signals, such as those used in 5G, 4G/LTE, and Wi-Fi applications.

High-Performance and Versatile USB Power Sensors

The Boonton PMX40 Power Meter utilizes Boonton RTP and CPS families of USB RF power sensors with industry leading performance and capabilities. All RTP sensors incorporate the unique Boonton Real-Time Power Processing™ technology, which virtually eliminates gaps in measurement suffered by other power sensors and enables industry best measurement speeds. In terms of RF performance, the RTP5000 series Real-Time Peak Power Sensors are the fastest responding sensors with 3 ns rise times and 195 MHz of video bandwidth. The RTP4000 series Real-Time True Average Power Sensors enable the lowest frequency measurements for diode-based average power measuring sensors and can make accurate measurements virtually independent of signal modulation bandwidth. CPS sensors offer flexible connectivity and performance leadership at an excellent price point.

RTP5000 Series Real-Time Peak Power Sensors

- 50 MHz to 6 GHz, 8 GHz, 18 GHz and 40 GHz peak RF power sensors
- Up to 195 MHz video bandwidth with 3 ns rise time
- Crest factor and statistical measurements (e.g., CCDF)
- 10 GS/s effective sample rate

RTP4000 Real-Time True Average Power Sensors

- 4 kHz to 6 GHz and 10 MHz to 6 GHz and 18 GHz average RF power sensors
- No modulation bandwidth limitations
- 1 GS/s effective sample rate

CPS2008 True Average Connected Power Sensors

- 50 MHz to 8 GHz
- 60 dB dynamic range
- USB and LAN (PoE) connectivity
- Most cost-effective average RF power sensor in its class

All RTP Real-Time Power Sensors

- Real-Time Power Processing™ technology with virtually zero measurement latency
- 100,000 measurements per second
- 80 dB dynamic range
- Synchronized multi-channel measurements



Software Features


Real-Time Power Processing™

Boonton Real-Time Power Processing¹ dramatically reduces the total cycle time for acquiring and processing power measurement samples. By combining a dedicated acquisition engine, hardware trigger, integrated sample buffer, and a real-time optimized parallel processing architecture, Real-Time Power Processing™ performs most of the sweep processing steps simultaneously, beginning immediately after the trigger instead of waiting for the end of the acquisition cycle.

The advantages of the Real-Time Power Processing technique are that key processing steps take place in parallel and keep pace with the signal acquisition. With no added computational overhead to prolong the sweep cycle, the sample buffer cannot overflow. As a result, there is no need to halt acquisition for trace processing. This means gap-free signal acquisition virtually guarantees that intermittent signal phenomena such as transients or dropouts will be reliably captured and analyzed.


¹ RTPP is available within the RTP500 and RTP4000 sensors.

Dropouts, such as those shown left, are the sorts of events often missed by conventional power meters due to the acquisition gaps while processing takes place.



Measurement Buffer Mode

The RTP series Measurement Buffer Mode is a remote control function that works in conjunction with Real-Time Power Processing to provide only the relevant burst or pulse information, eliminating the need to download and post-process large sample buffers. As a result, users can collect and analyze measurements from a virtually unlimited number of consecutive pulses or events without gaps. A wide variety of parameters can be calculated and plotted, such as duty cycle, pulse repetition rate, pulse width variation, and pulse jitter. In addition, anomalies, such as dropouts, can be identified.



Example seven pulse waveform.

Entry Count	Interval Start	Interval Duration	Interval Average	Interval Minimum	Interval Peak
0	0.00 us	5.01 us	-0.043 dBm	-39.042 dBm	8.826 dBm
1	9.99 us	5.00 us	-0.006 dBm	-38.431 dBm	8.827 dBm
2	19.99 us	5.01 us	0.039 dBm	-41.549 dBm	9.742 dBm
3	30.00 us	5.00 us	0.017 dBm	-38.551 dBm	9.802 dBm
4	40.01 us	5.00 us	0.022 dBm	-40.699 dBm	9.477 dBm
5	49.99 us	5.00 us	-0.020 dBm	-39.706 dBm	8.102 dBm
6	60.00 us	5.00 us	0.036 dBm	-37.803 dBm	9.750 dBm


Measurement buffer data returned for waveform in above.

PMX40 RF Power Meter


Addressing RF Communications and Radar Measurement Challenges

Wi-Fi and Wireless Communication Signal Analysis

Characterization and compliance testing of Wi-Fi and LTE chipsets and devices involves significant challenges for design and test engineers. With multiple-input, multiple-output (MIMO) architectures and channel bandwidths up to 160 MHz, testing is complex, especially when measuring RF power per channel and time alignment between channels. The PMX40 enables packet power measurements to be performed independently on multiple synchronous or asynchronous transmit chains with a common timebase shared among sensors.




Use markers to define a portion of the waveform on which to make measurements. **“Between Marker” measurements** are ideal for monitoring specific portions of a packet over long intervals.



Video bandwidth (VBW) describes the ability of a power sensor to track peak (envelope) power. Insufficient VBW will result in errant envelope and average power measurements. The PMX40 offers the **widest video bandwidth (195 MHz)** making it ideal for measuring 80 MHz, 100 MHz, and 160 MHz channels.



By comparing the peak-to-average power ratio, or crest factor (CF), of input and output signals of an RF transmission chain, engineers can assess circuit linearity. Additional insight can be provided with the PMX40 statistical mode **Complementary Cumulative Distribution Function (CCDF)** plot displaying the rate of occurrence of a specific CF. As an amplifier output compresses, the CF will reduce and the CCDF plot will move left.




PMX40 RF Power Meter


Addressing RF Communications and Radar Measurement Challenges

Secondary Surveillance Radar (SSR)

Design, verification, troubleshooting and maintenance of secondary surveillance radar (e.g. IFF-based radar) has never been more demanding.



Proper design and operation of SSR systems is critical to the the safety and security of aviation. The PMX40 can be used to easily and accurately capture SSR waveforms. Markers enable measurements on specific portions of the waveform.



Industry-leading rise time (<3 ns) enables characterization of the most demanding radar signals.

Utilize the **superior 100 ps time resolution** to zoom and uncover signal characteristics that might otherwise be missed.

Param	CH1	CH2
Width	30.080 μ s	30.012 μ s
Rise	21.061 μ s	21.132 μ s
Fall	22.395 μ s	23.404 μ s
Period	999.77 μ s	999.89 μ s
PRF	1.0002 kHz	1.0001 kHz
Duty	3.01%	3.00%
Offtime	969.69 μ s	969.88 μ s
WavAv	-14.158 dBm	-5.348 dBm
PulsAv	0.484 dBm	9.445 dBm
PulsPk	1.327 dBm	10.098 dBm
OvrSht	0.290 dB	0.110 dB

Users can take advantage of the PMX40 **automated pulse measurement** feature to measure and calculate 16 common power and timing parameters and display the parameters of interest: rise-time, fall time, pulse width, off-time, period, pulse repetition frequency, duty cycle, pulse peak, pulse overshoot, pulse average, waveform average, top level power, droop, bottom level power, edge delay, and pulse edge skew between channels.


Sensor Software

Power Analyzer - Advanced Measurement and Analysis Software

Power Analyzer is a complimentary PC-Based software package for RTP5000 and RTP4000 sensor control, measurement configuration, and advanced analysis. It includes USB drivers, remote control API, firmware updater and virtual instrument application.

Key Features and Functionality

- Data displayed as numerical meter or waveform trace
- Statistical analysis with CCDF plot
- Multiple marker measurements, including between marker data and marker ratios
- Automated measurements; e.g., 16 automated pulse measurements
- Export measurement data in .csv or .pdf formats
- Up to 8 simultaneous power measurement channels
- Simulation mode available to preview functionality when a sensor is not available




Power Viewer – Simple and Intuitive Measurement Software

Power Viewer is a complimentary PC-based software package for CPS2008 sensor control, measurement configuration, and analysis. It includes USB drivers, remote control API, firmware updater and virtual instrument application.

Key Features and Functionality

- Large numeric readout and/or analog meter display
- Zoom and pan through data logging strip chart
- Quickly set frequency, aperture (averaging) and offset values all from the main screen
- Calculates ratios between sensor measurements
- Control up to 8 sensors at once
- Simulation mode available to preview functionality when a sensor is not available



Sensor Specifications

	RTP5006	RTP5008	RTP5318	RTP5518	RTP5340	RTP5540
RF Frequency Range	50 MHz to 6 GHz	50 MHz to 6 GHz	50 MHz to 18 GHz	50 MHz to 18 GHz	50 MHz to 40 GHz	50 MHz to 40 GHz
Dynamic Range						
Average	-60 to +20 dBm	-60 to +20 dBm* -53 to +20 dBm†	-34 to +20 dBm	-50 to +20 dBm	-34 to +20 dBm	-50 to +20 dBm
Pulse	-50 to +20 dBm	-50 to +20 dBm* -43 to +20 dBm†	-24 to +20 dBm	-40 to +20 dBm	-24 to +20 dBm	-40 to +20 dBm
Internal Trigger						
Range	-38 to +20 dBm	-38 to +20 dBm	-10 to +20 dBm	-27 to +20 dBm	-10 to +20 dBm	-27 to +20 dBm
Min Pulse Width (fast/std)	10 ns / 3 µs	10 ns / 3 µs	10 ns / 3 µs	200 ns / 3 µs	10 ns / 3 µs	200 ns / 3 µs
Max Repetition Rate	50 MHz	50 MHz	50 MHz	5 MHz	50 MHz	5 MHz
Rise time (fast/std)	3 ns / < 10 µs	4 ns / < 10 µs	5 ns / < 10 µs	< 100 ns / < 10 µs	5 ns / < 10 µs	< 100 ns / < 10 µs
Video Bandwidth (high/std)	195 MHz / 350 kHz	165 MHz / 350 kHz	70 MHz / 350 kHz	6 MHz / 350 kHz	70 MHz / 350 kHz	6 MHz / 350 kHz
Single-shot Bandwidth	35 MHz	35 MHz	35 MHz	6 MHz	35 MHz	6 MHz
RF Input	Type N, 50 Ω	Type N, 50 Ω	Type N, 50 Ω	Type N, 50 Ω	2.92 mm, 50 Ω	2.92 mm, 50 Ω
VSWR	1.25 (0.05 - 6 GHz)	1.20 (0.05 - 6 GHz) 1.25 (6 - 8 GHz)	1.15 (0.05 - 2.0 GHz) 1.28 (2.0 - 16 GHz) 1.34 (16 - 18 GHz)	1.15 (0.5 - 2.0 GHz) 1.20 (2.0 - 6.0 GHz) 1.28 (6.0 - 16 GHz) 1.34 (16 - 18 GHz)	1.25 (0.05 - 4.0 GHz) 1.65 (4.0 - 38 GHz)	1.25 (0.05 - 4.0 GHz) 1.65 (4.0 - 38 GHz)

* From 50 MHz to 6 GHz † From >6GHz to 8 GHz

	RTP4006	RTP4106	RTP4018-S/1	CPS2008
RF Frequency Range	10 MHz to 6 GHz	4 kHz to 6 GHz	10 MHz to 18 GHz	50 MHz to 8 GHz
Dynamic Range				
Average	-60 to +20 dBm	-60 to +20 dBm	-60 to +20 dBm	-40 to +20 dBm
Pulse	-45 to +20 dBm	-45 to +20 dBm		
Internal Trigger				
Range	-40 to +20 dBm	-40 to +20 dBm	-40 to +20 dBm	
Min Pulse Width (fast/std)	4 µs	4 µs	4 µs	
Max Repetition Rate	120 kHz	120 kHz	120 kHz	
		1.26 (4.0 GHz to 6.0 GHz)		
RF Input	Type N, 50 Ω	Type N, 50 Ω	SMA, 50 Ω	Type N, 50 Ω
VSWR	1.15 (0.01 - 2 GHz) 1.20 (2.0 - 4.0 GHz) 1.26 (4.0 to 6.0 GHz)	1.15 (0.01 - 2.0 GHz) 1.20 (2.0 - 4.0 GHz) 1.26 (4.0 to 6.0 GHz)	1.15 (0.01 - 2.0 GHz) 1.25 (2.0 - 12.4 GHz) 1.35 (12.4 to 16 GHz) 1.45 (16 to 18 GHz)	1.3 (0.05 - 8 GHz)



Specifications


Channels	Up to 4	
Sensors	RTP5000 Series RTP4000 Series CPS2000 Series	
Display	5-inch WVGA multi-touch display with intuitive graphical user interface	
Display Modes	Trace (power vs time) Statistical measurements Automatic measurements (pulse, statistical, and markers measurements)	Meter (numeric display) CCDF
Marker Measurements (in Trace View)	Markers (vertical cursors) Marker Independently Interval Between Markers Pair of Markers	Settable in time relative to the trigger position Avg, Min and Max Power at a specified time offset Avg, Min and Max Power over the defined interval Ratio of power values at each marker
Pulse Mode – Automatic Measurements	Pulse rise-time Pulse width Pulse period Pulse duty cycle Pulse peak Pulse overshoot Top level power Edge delay	Pulse fall-time Pulse off-time Pulse repetition frequency Waveform average Pulse average Pulse droop Bottom level power Pulse edge skew between channels
Statistical Mode – Automatic Measurements	Peak power Minimum power Dynamic range Crest factor at cursor	Average power Peak to average ratio Percent at cursor Crest factor at various percents
Trigger	Synchronization* Mode Source Internal Level Range External Level Range Slope Hold-off, Min Pulse Width, Max Trigger Rate	Among RTP Series (internal trig distribution) Normal, Auto, Auto Pk-to-Pk, Free Run Any connected RTP Series sensor (via SMB's) or rear panel external trigger -40 dBm to +20 dBm (sensor dependent) ±5 volts or TTL + or - Sensor and timebase dependent
Time Base	Time Base Resolution, Range, Accuracy Time Base Display Trigger Delay Range Trigger Delay Resolution	Sensor dependent Sweeping or Roll Mode Sensor dependent 0.02 divisions

Specifications, Continued

Inputs/Outputs (front panel)	USB with SMB trigger port	4 ports USB2.0: Type A receptacle 4 ports SMB(f)
Test Source (optional rear panel placement)	50 MHz	1.00 mW (0 dBm) +/- 2.3% (0.1 dB) typ
Inputs/Outputs (rear panel)	LAN	10/100 Ethernet: RJ-45 modular socket
	USB with SMB trigger port	4 ports USB2.0: Type A receptacle 4 ports SMB(f)
Remote Control	Command Set	SCPI-1999.0
	LAN	Ethernet:10/100/1000 BaseT; HiSLIP
	GPIB (optional)	
Regulatory Compliance	CE compliance with the following European Union directives Low Voltage Directive 2014/35/EU Electromagnetic Compatibility Directive (EMC) 2014/30/EU RoHS Directive EU 2015/863, WEEE Directive 2012/19/EU Manufactured to the intent of MIL-PRF-28800F, Class	
Construction	Manufactured to the intent of MIL-PRF-28800F, Class	
Dimensions (excluding connectors)	H x W x D	3.5x8.3x11.2 (in),89x211x284 (mm)
Weight	4.8 lbs, 2.2 kg	
AC Power		
Rated Voltage	100 to 240 VAC	
Voltage Range	90 to 264 VAC	
Rated Frequency	50/60 Hz	
Frequency Range	47 to 63 Hz	
Power Consumption	60 W (70 VA) max, 30 W (35 VA) nominal with no external peripheral devices attached	
Operating Temperature	0 to 50 °C (32 to 122 °F)	
Storage Temperature	-40 to +70 °C (-40 to 158 °F)	
Humidity	95% maximum, non-condensing	
Altitude	Operation up to 15,000 feet (4,575 m)	
Warranty	3 years	

This instrument is designed for indoor use only

- 1 Optional GPIB connectivity
- 2 External trigger input
- 3 Auxiliary sensor and Sync inputs
- 4 HDMI output for remote front panel display
- 5 LAN connectivity
- 6 Optional Test Source rear panel output



Ordering Information

PMX40 RF Power Meter (includes 2 active channels)

Options

PMX40-4CH	Adds 2 Active Channels (for a total of 4)
PMX40-GPIB	GPIB Control (internally installed)
PMX40-RTS	Moves Test Source output to the rear panel
PMX40-SECURE	Removes internal microSD and enables boot from USB drive (included)
PMX40-2SECOP	Installation of PMX40-SECURE post initial purchase (retrofit); requires return to factory

Included Accessories

Information Card (provides information on where to download the latest manual, software, utilities)

Optional Accessories

PMX40-RMK	Full-width 19" Rack Mount Kit (includes handles & hardware for mounting one or two meters)
PMX40-TCASE	Transit case, hold the PMX40 and up to 4 sensors
PMX40-RSSD	Additional external USB drive for secure operation

RF Power Sensors

CPS2008	True Average Connected Power Sensor	50 MHz to 8 GHz
RTP4006	Real-Time True Average Power Sensor	10 MHz to 6 GHz
RTP4106	Real-Time True Average Power Sensor	4 kHz to 6 GHz
RTP4018-S/1	Real-Time True Average Power Sensor	10 MHz to 18 GHz
RTP5006	Real-Time Peak Power Sensor	50 MHz to 6 GHz
RTP5008	Real-Time Peak Power Sensor	50 MHz to 8 GHz
RTP5318	Real-Time Peak Power Sensor	50 MHz to 18 GHz
RTP5518	Real-Time Peak Power Sensor	50 MHz to 18 GHz
RTP5340	Real-Time Peak Power Sensor	50 MHz to 40 GHz
RTP5540	Real-Time Peak Power Sensor	50 MHz to 40 GHz

Included Accessories

Information Card (provides information on where to download the latest manual, software, utilities)

- 0.9 m BNC (m) to SMB (m) cable (RTP sensors)
- 0.9 m SMB (m) to SMB (m) cable (RTP sensors)
- 1.8 m USB A (m) to USB B (m) locking SeaLATCH cable (RTP sensors)
- 1.6 m USB A (m) to USB B (m) cable (CPS sensors)

Specifications and performance subject to change

Wireless Telecom Group Inc.
25 Eastmans Rd
Parsippany, NJ
United States
Tel: +1 973 386 9696
Fax: +1 973 386 9191
boonton.com